


Conectores rectos

Rosca BSP (gas) recta, teflonada o con o'ring



Modelo	10.000 al 10.018-CR...-...
Fluido	Aire, Vacío y Líquidos
Rango de Presión	-0,75 a 10,2 bar
Vacío	-0,750 mm Hg (10 Torr)
Presión Máxima	15,3 bar
Conexión	Rosca de M5 a 1/2"
Diámetro de Manguera	de 4 mm a 16 mm
Temperatura	0 a 60 °C



CÓDIGO	MODELO	D1	D2	L1	L2	LLAVE	ALLEN
10.000	CR 4 M5	4	M5	21,5	2,5	10	
10.001	CR 4 1/8"	4	1/8"	22	4	10	3
10.002	CR 6 1/8"	6	1/8"	26	5	12	4
10.003	CR 8 1/4"	6	1/4"	22,5	5,5	12	5
10.004	CR 8 1/8"	8	1/8"	23	6,4	14	5
10.005	CR 8 1/4"	8	1/4"	26	6	14	6
10.006	CR 8 3/8"	8	3/8"	24,5	8	14	6
10.007	CR 10 1/4"	10	1/4"	30,5	5,5	17	6
10.008	CR 10 3/8"	10	3/8"	30	9,7	17	8
10.009	CR 10 1/2"	10	1/2"	31	9	17	8
10.010	CR 12 1/4"	12	1/4"	31	7	21	6
10.011	CR 12 3/8"	12	3/8"	28	7,5	21	10
10.012	CR 12 1/2"	12	1/2"	32,5	10	21	8
10.013	CR 6 M5	6	M5	22,5	53	12	1,5
10.014	CR 4 1/4"	4	1/4"	16,5	5,7	1	3
10.016	CR 6 M6	6	M6	23	4	12	2
10.017	CR 16 1/2"	16	1/2"	38	10	24	8
10.018	CR 8 1/2"	8	1/2"				6

Reservado el derecho de modificación sin previo aviso



+54 911 5486 0664



011 2199 7887

ventas@dineu.com.ar

www.dineu.com.ar



DiNeu[®]
Pneumatics